



INSTALLATION INSTRUCTIONS

4388 N. Carson St., Carson City, NV | Customer Support: 805.988.2900 | Fax: 805.988.2948 | www.gbrakes.com

YEAR: 2025	MAKE: Kawasaki 2 line kits	MODEL: ZX4rr
PRODUCT # FK003D1075-2	PRODUCT DESCRIPTION:	Front ABS delete Brake Line Kit
LIFETIME WARRANTY		

When installing your new GBrakes brake lines, please be sure to note what type of kit you have purchased. 2-line kit, ABS delete kit,; also note the type of fittings you have received, since torque specs may vary. Please remember that your new GBrakes brake lines will route differently than your stock hoses and will not use the stock rings. GBrakes uses the terms “right” and “left” as if you were sitting on the bike. GBrakes brake lines have a limited lifetime warranty

INSTALLATION

This kit will run a single line from the master cylinder down right caliper. Install Using short bolt, washer, banjo, washer. Install the other end to caliper, Using long bolt, washer, banjo, washer crossover line, mount line to caliper use bolt washer install The crossover line to the right caliper over the fender to the left caliper Install Using short bolt, washer, banjo. washer torque all bolt to proper spec

.TORQUE SPECS: Stainless Steel 15-17 ft lbs Aluminum 12-15 ft lbs

Before proceeding to the next step, please check for clearance of the lines. Compress the suspension to make sure that the lines are not binding with anything when the front and rear end are fully extended or fully compressed. Double check the lines, making sure they are traveling correctly and are clear from any obstructions.

Bleed brake system according to owner’s manual. And build appropriate pressure. Finish with DOT-4 brake fluid.

Once the bleeding has been done, please check brake fluid level on master cylinder. Close brake fluid reservoir, and zip-tie the brake lever to the throttle for at least 2 hours to ensure no leaks or other possible issues. For the rear, set a jug or something similar on the brake pedal to apply pressure. If the lines are not leaking and all looks OK (bolts are tight, washers in between), you may now ride with the new system. Make sure the rider is aware that the overall braking feel has dramatically changed. We suggest taking it easy to get used to the new brake lever feel and pressure. We recommend checking your brake system periodically; keep in mind brake lines must be checked **very** carefully! If there are any signs of damage or stress to the lines, the complete brake system must be replaced. Remember, our brake lines have a LIFETIME WARRANTY! If you have any problems or questions, don’t hesitate to call us at **(805) 988-2900**.